

PERFORMANCE FITNESS FLOORING INSTALLATION

Storage / Pre-Installation

- Store tiles in a dry and clean area
- Tiles must be installed on a clean, dry, and level subsurface
- At least 24 hours before starting the installation lay out all tiles on the subsurface top allow them to acclimate (this will ensure tiles are an accurate size and thickness)
- In-floor radiant heat should be shut off for 24 hours prior to the installation
- Interlocking rubber tiles should not be installed on top of carpet as the tiles will shift apart

Measuring & Cutting

- If cuts are required, measure the desired length from the outside tab inwards
- Lay tile on a flat surface, hold a metal straight edge on the desired cut line, and cut with a sharp utility knife
- Keep scoring the cut until separated, change or snap off blades frequently to ensure clean cuts

Installation

- Begin installation in the center point of room working outwards towards wall
- Assure a tight fit by tapping tiles together as they are being installed
- In order to create a finished straight edge be sure to trim off interlocking tabs
- Make sure all tiles are laid down with "arrow" pointing in the same direction

Maintenance

- To clean mats vacuum, then damp mop with warm water using a neutral cleaner
- Products containing mineral solvents and acids will attack the composite structure of the rubber flooring and cause deterioration
- Do not use wax on the recycled rubber flooring
- When cleaning equipment/furnishings with disinfectant or other strong cleaners, be careful that overspray or excess cleaner does not drip onto the rubber flooring. Strong chemicals may cause the surface to deteriorate



5 Year Limited Warranty – Tiles will be free from defects in material and workmanship under normal use for 5 years. No other part or component of the product or installation of the product is warranted.

ENGINEERED
TO **OUT** PERFORM

Rubber King is a proud manufacturer of North American made products. We want the best for you and your family, that's why we offer only FloorScore® certified products, lending peace of mind to every purchase.