

ROUTINE MAINTENANCE EXTENDS LIFE AND ENHANCES APPEARANCE

A. Upon Receipt of Product:

The tiles are coated with a water-based mold release residue, a natural result of the manufacturing process. This will initially cause slight discoloration and slipperiness. For fast removal, apply a solution of neutral cleaner (scented or non scented) and agitate with brush or mop, then rinse with water. Exposure to sun and rain will naturally remove this residue however the process may take up to four weeks, depending on local weather conditions.

B. Cleaning and Maintenance:

Sweeping, vacuuming and damp mopping of the surface are the most common methods of keeping the tiles clean (indoor use). If the surface is excessively dirty, apply a solution of neutral cleaner and water, agitate with a brush and rinse with water. Outdoor installations may incorporate the use of a water hose however **do not use a pressure washer to clean the tiles. Do not use solvents of any kind.**

All food and drink should be restricted from the installation area as best as possible. In the event that a spill has occurred the tiles should be cleaned as follows:

Use a wet-vac immediately to remove as much liquid as possible. Scrub the tiles with a soft brush and mild detergent then rinse with minimal water. Excess water should be drained into floor drains or use the wet-vac to clean any liquids that have drained through the tiles. To prevent odor, bacteria growth, etc. all excess liquids must be removed. If necessary, tiles may be removed and cleaned thoroughly. Be sure that the tiles are completely dry and free of foreign material before re-installing.

C. Installation:

