



## **Cleaning & Maintenance Guideline Square Cut Indoor Rubber Flooring**

### **A) Post Installation Cleaning**

- When flooring installation is complete and adhesive is fully cured, sweep floor to remove any debris, then dust mop thoroughly to remove all surface dust and dirt using a dust mop or microfiber mop.
- Damp mop using a neutral PH cleaner diluted with warm water using a microfiber mop. (See dilution rate on label)
  - Use a two-bucket system and change the water frequently.
  - Do not use any oil base cleaners as they will deteriorate the mats.
- If floor has been unprotected during construction and an excessive amount of dirt or dust is present additional cleaning with an auto scrubber may be required.
  - An RPM of 185 and brush pressure between 35lbs and 85lbs are recommended
  - If disc type equipment is used, be sure to use a soft nylon brush, not a pad.
- Do not flood the floor.
- Allow to dry thoroughly.
- Apply a treatment of an acrylic polymer floor coating according to the instructions on the label if desired.

### **B) General Maintenance**

- Typically, Rubber King Commercial products require less maintenance than other types of flooring.
  - Sweeping then damp mopping with a microfiber mop is the preferred method.
    - Do not use a string mop.
  - Use a two-bucket system with a neutral PH cleaner and change water frequently.
  - Products containing solvents and acids will attack the composite structure of the rubber flooring and cause deterioration.
  - Sealants, waxes, etc can alter the surface characteristics and appearance.
    - Rubber King Commercial does not assume any responsibility for damages caused by chemical additives.
  - If an acrylic polymer protective floor coating is used, be sure to reapply after cleaning.

### **C) Floor Treatment**

- For most installations, it is not necessary to seal or coat Rubber King Commercial products.
  - Contact your supplier for the correct choice in your application.
- An acrylic polymer floor coating is recommended to improve the visual effects of shade variation and uneven distribution of color granules.
  - See label for installation instructions.

**For additional information or technical assistance, please contact your Rubber King Commercial supplier.**

**Rubber King Commercial**  
Website: [www.rubberking.com](http://www.rubberking.com)

**Tol Free: 1-855-663-1520**  
E-mail: [commercial@rubberking.com](mailto:commercial@rubberking.com)